

R304217 Central Loose Tube Cable A-D(ZN)W2Y, G.652.D, 24-fibers

030.1422 Similar product

**Description**

The outdoor cable for applications in harsh conditions. It contains a central gel-filled loose tube of a diameter of 2.8 mm for 2 - 16 fibers or 3.5 mm for 18 - 24 fibers. The outer sheath is made of a 0.155 mm corrugated steel armor plus a 1.5 mm PE sheath.

Sheath: PE, black.

Fiber: singlemode (SM) E9/125.

Weight

0.000G

Technical Data

Standardisation	ISO/IEC 11801:2002 ITU-T G.652.D IEC 60793-2-50:2004, B 1.3 IEC 60794-1-2 E1; IEC 60794-1-2 E11; IEC 60794-1-2 E3; IEC 60794-1-2 F1; IEC 60332-1; IEC 60332-3C; IEC 61034; IEC 60754-2
Cable class	Loose Tube
Cable design	A-D(ZN)W2Y
Fiber class	G.652.D (OS1, OS2)
Number of fibers / conductors	24
Cable jacket material	PE
Cable jacket characteristics	cable, water-tight
Cable jacket characteristics	zero-halogen
Cable protection	steel-armored
Cable overall diameter	9.5 mm
Conductor type	loose tube, gel-filled
Fiber / conductor diameter	E9/125µm
Fiber type	Singlemode (SM)
Color	black
Length (meter)	2000